

Mechanical Vice Grip


Rated 5 kN (1125 lb)

G56G-5-15	
Opening	0 – 15 mm (0.6")
Weight	1.04 kg (2.3 lbs) each without jaws
G56G-5-43	
Total height	220 mm (8.7")
Distance between lower edge of jaws and coupling	200 mm (7.9")
Opening	0 – 44 mm (1.7")
Weight	1.7 kg (3.7 lbs) each without jaws
G56G-5-15 and G56G-5-43	
Tensile force	5 kN (1125 lbs)
Temperature range	0°C – 180°C (32° – 356°F)
Body	Anodized aluminum



Interchangeable Hardened Steel Jaws or Faces

Jaw	Description	Opening G56G-5-15	Opening G56G-5-43
J56G-B	Blank jaws 30 x 50 mm	0 – 15 mm	0 – 44 mm
J56G-BG	Rubber jaws 30 x 50 mm	0 – 13 mm	0 – 42 mm
J56G-BP	Pyramid jaws 30 x 50 mm	0 – 15 mm	0 – 44 mm
J56G-BV2	V-jaws 30 x 50 mm	Ø 2 – 15 mm	Ø 2 – 41 mm
J56G-BV5	V-jaws 30 x 50 mm	Ø 5 – 11 mm	Ø 5 – 41 mm
J56G-BW	Wave jaws 30 x 50 mm	0 – 15 mm	0 – 44 mm
J56G-BD	Diamond jaws 30 x 50 mm	0 – 15 mm	0 – 44 mm



Rubber coated V-jaws

